


CLIFF

CAT6 RJ45 RIGHT ANGLE FEEDTHROUGH CONNECTOR (RAFT)



2x FIXING HOLE VARIANTS:
Ø3.5mm CSK 82° x Ø5.85
'X' VERSION HAS Ø2.5 PLAIN HOLES.

HOLES TO SUIT
SCREW USED

PANEL CUTOUT
MAXIMUM PANEL
THICKNESS 2mm

VARIANTS

Part No.

CP30252 RAFT Cat6 RJ45 Black plastic frame, CSK holes

CP30252X RAFT Cat6 RJ45 Black plastic frame, 2.5mm PLAIN holes

Feedthrough Features

- Fits standard XLR Ø24mm cutout.
- No soldering or punch termination. Use standard cable for each connector style.
- Front or rear mounted.
- Low rear profile
- 90° or right angle rear cable entry.

Material:

1. RJ45 In-Line Coupler: ABS UL94-V2
2. RJ45 In-Line Coupler Contact: Phosphor Bronze, gold plating.
3. PCB: FR4
4. Frame: Polyamide UL94-V2

General:

Please note: Functionality is affected by cable quality, length and cable wiring configuration.

Performance:

1. T568A & T568B wiring.
2. Meet ISO/IEC 11801 and EN50173
3. Meet ANSI/TIA/EIA 568B.2
4. Rating 125VAC RMS 1.5A
5. Operating Temperatures: Min -10°C Max +60°C