

SPECIFICATIONS

DRAWN: T.J.O.

Contact Resistance : 30mΩ max

Insulation Resistance : 100MΩ min at DC 500V

Dielectric Withstanding Voltage : AC 500V for 1 minute

Cliff Electronic Components Ltd.

76 Holmethorpe Avenue, Holmethorpe Industrial Estate,
Redhill, Surrey, RH1 2PF, England, UK Tel: 01737-771375 Fax: 01737-766012 Website: www.cliffuk.co.uk THE CONTENTS OF THIS DOCUMENT MUST NOT BE COPIED OR DISCLOSED

TO A 3rd PARTY WITHOUT WRITTEN PERMISSION OF CLIFF UK. © 2014

DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE STATED. WORK TO DIMENSIONS. REMOVE ALL BURRS. IF IN DOUBT ASK. SEE TABLE MATERIAL:

3rd ANGLE PROJECTION:



UNLESS OTHERWISE STATED

HOLE Ø ± ANGLES ±

VCOMPLIANT

TOLERANCE

1 DEC. PLACE ±

2 DEC. PLACE ±

AMEND

ISSUED

DATE 10/10/14

TITLE: LOCKING DC PLUG Ø2.5mm + Ø2.1mm (REWIRE TYPE) CLEAN FINISH:

APPROVED: D.P.J.

DRWG. No.

DO NOT SCALE

FC6814775

FORM: A4DRWGH